

MISSOURI DEPARTMENT OF HEALTH STATE PUBLIC HEALTH LABORATORY

DATAMASTER MAINTENANCE REPORT

Complete #	n i	$ \sim$ \sim \sim \sim \sim \sim	LEOUGL BREEKELD
Complete this report in duplicate at the time of the regul	or mouth.		LCOHOL PROGRAM
Complete this report in duplicate at the time of the regule is repaired. Send copy to Department of Health; retain origin	at monthly preventive mainte	nance chec	k and whenever instrume
201197	- partition ine.		LE OF INSPECTION
LOCATION OF INSTRUMENT (STREET AND CITY)		OHSS \$17	6-1-0-911
// 1 1000 - 11		711	5 05 N/05
	<u>mo</u> 63050		08:30
CHECKLIST: Place a check (*) to the left of each item if to observed values where determined.) Unchecked items must DIAGNOSTIC CHECK (PROVIDED IN THE PROVIDED	ound to be satisfactory or if of	perating with	nin established limits. (Wr
DIAGNOSTIC CHECK (PRINTOUT ATTACHED)	to corrected before using in	istrument.	<u> </u>
CONTRACTOR ATTACHED)			
COMPUTER	[45		
PROGRAM	DETECTOR		
	FILTERS		
HEATERS SAMPLE CHAMBER 48 °C			
	QUARTZ STANDARD)	
FLOW DETECTOR			
PUMP HIGH SPEED	CALIBRATION	. <u> </u>	
	PRINTER	· · · · · ·	
INDICATOR LIGHTS			
TIME AND DATE			
SIMULATOR TEMPERATURE			_
SIMULATOR TEMPERATURE (34 °C ± 0.2°C) 34.6	5 C		
CACIBRATION CHECK -		<u>-</u>	
nut three tests using a standard solution. All three too	oto militari		
spread of .005 or less. Check the box corresponding to	sts must be within ± 5% of	the standar	d value and must have a
Run three tests using a standard solution. All three test spread of .005 or less. Check the box corresponding to RECIRCULATION PUMP)		the standar used. (PRIN	d value and must have a
E 0.100% STANDARD MUST DE LA	- Jones Long (the standardused. (PRIN	d value and must have a TOUT ATTACHED) (USE
O.100% STANDARD - MUST READ BETWEEN 0.095%	and 0.105% INCLUSIVE	the standar ⊔sed. (PRIN	d value and must have a
O.100% STANDARD - MUST READ BETWEEN 0.095% OO 0.040% STANDARD - MUST READ BETWEEN 0.038% ONLY ONE STANDARD IS TO BE USED PER MAINTEN.	and 0.105% INCLUSIVE	the standardused. (PRIN	d value and must have a TOUT ATTACHED) (USE
O.100% STANDARD - MUST READ BETWEEN 0.095% O.0040% STANDARD - MUST READ BETWEEN 0.038% (ONLY ONE STANDARD IS TO BE USED PER MAINTEN,	and 0.105% INCLUSIVE	the standardused. (PRIN	d value and must have a
O.100% STANDARD - MUST READ BETWEEN 0.095% : 0.040% STANDARD - MUST READ BETWEEN 0.038% : (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT)	associ. (Fring	(USE
O.100% STANDARD - MUST READ BETWEEN 0.095% : 0.040% STANDARD - MUST READ BETWEEN 0.038% : (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT)	the standardused. (PRIN	d value and must have a TOUT ATTACHED) (USE
O.100% STANDARD - MUST READ BETWEEN 0.095% OO 0.040% STANDARD - MUST READ BETWEEN 0.038% ONLY ONE STANDARD IS TO BE USED PER MAINTEN. EST 1 TEST 2 TEST (PRINTOUT ATTACHED)	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT)	ST3 F	/01%
O.100% STANDARD - MUST READ BETWEEN 0.095% OO 0.040% STANDARD - MUST READ BETWEEN 0.038% ONLY ONE STANDARD IS TO BE USED PER MAINTEN. EST 1 TEST 2 TEST (PRINTOUT ATTACHED)	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT)	ST3 F	1001 ATTACHED) (USE
O.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT)	ST3 F	. /O/ %
D 0.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	ST3 F	1001 ATTACHED) (USE
D 0.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	EST 3 F	. /O/%
D 0.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	EST 3 F	. /O/%
D 0.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	EST 3 F	. /O/%
D 0.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	EST 3 F	. /O/%
D 0.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	EST 3 F	. /O/%
D 0.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	EST 3 F	. /O/%
D 0.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	REATH TEST	. /O/%
D.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% EPORT, AND NUMBER OF BE (.1014) / (.151) I that was made to restore the conditions of	REATH TEST	(Over .19)
D.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% TEPORT, AND NUMBER OF BE	REATH TEST	(Over .19) Don't to operate satisfactorily
D.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /00% TEPORT, AND NUMBER OF BE (.1014) / (.151) I that was made to restore the content of th	REATH TEST	(Over .19)
D.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /co% EPORT, AND NUMBER OF BE (.1014) / (.151) I that was made to restore the conditions of	REATH TEST	(Over .19) D If to operate satisfactorily E Ethoric Chiper
D.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - 100% TEPORT, AND NUMBER OF BE (.1014)	REATH TEST	(Over 19) D If to operate satisfactorily 8 EHM C Uapar
D.100% STANDARD - MUST READ BETWEEN 0.095%: 0.040% STANDARD - MUST READ BETWEEN 0.038%: (ONLY ONE STANDARD IS TO BE USED PER MAINTEN, EST 1	and 0.105% INCLUSIVE and 0.042% INCLUSIVE ANCE REPORT) - /00% TEPORT, AND NUMBER OF BE (.1014) / (.151) I that was made to restore the content of th	REATH TEST 19) ie instrument	(Over 19) D If to operate satisfactorily 8 EHROLUAPOR



CERTIFICATE OF ANALYSIS

Certified Alcohol Reference Solution for Simulator

Random Samples of Lot Number 08400 of Alcohol Reference Solution for Simulator were analyzed by gas chromatography and found to contain 0.1204 percent (w/vol) ethyl alcohol. The expiration date for this lot number is December 8, 2009 at 11:59 PM.

When used in a calibrated Simulator, operating at 34°C +/- .2°C, this solution will give a breath alcohol analysis instrument reading of 0.10 percent BAC.

The alcohol and water used in this solution were free of test interfering substances.

Ted L. Pauley, President GUTH LABORATORIES, INC.

BAC DataMaster Evidence Ticket

STATE OF MILLOURI HILLSBORG POLICE DEPARTMENT

BAC IATAMASTER SERIAL NUMBER 201197 26/01/09

TESTING OFFICER:
GARTH
DEFICER (.D.: 035)
FERMIT NUMBER: 820272
EXPIRATION DATE: 02/26/10
MISCELLAMEDLS DATE:
JUNE MAINT

THE BURBANION MODELLE

٠		•						1.
	SEES TEGT	DETERMENT VINERAL	BURNEY TOWN	DESCRIPTION OF THE PROPERTY OF	BUNDE OFFICE	MXTMXXXIC WITHXBEXO	INTERNAL STAMMEN	BEETS THAT
	Cens	. 135r	, <u>COO</u> O	13 2.	, ভারত	· 图: 图:	シアカレカ 上がた	· 在5000000000000000000000000000000000000
	5000 6000 6000 6000	e Ti	S	(A) (A) (A) (A)	\$31.34 4	66 100 100		<u>ن</u> ن ن

AVO. H.1

]2 |||

Operator Signature OACH #853

Face This Side Down - This Edge In First

BAC DataMaster Evidence Ticket

STATE OF MISSOURI

BAC INTERNASIEM SEMERE ROMIER ZÖLLST PÖZÖLZUZ BACLIKA ZÖNER

--- DO HANDLY OF CONTROL

A CUMPULLER

PRUSPINA USA

SAMPLE CHEMBER: 480

FLOW BETELTOR: UKA:

H16H SPEED: OKAY

건물시간

DETECTOR:

F1LTERS: UNHY

SUARIZ STANDÁRD: 1897

SEAS.

CHELLERAL LONG

ignature Openty #8

2208-02

Operator Signature___

18022

Face This Side Down - This Edge In First

BAC DataMasterEvidence Ticket

STATE OF MISSOURI HILLSBORD POLICE DEPARTMENT

BAC DATAMASTER SE-1AL NUMBER 201197 06/01/09

: ARREST TIME: 05:30 SUBJECT MAME: GARTA DOB: 01/01/8) SEX! "

STATE/D.L.: MOV. 234567 898

ARRESTING OFFICER:

GARTA

COMPTICES 1.D.: 0853

TESTING OFFICES:
GARTA

OFFICER 1.D.: 0853
PERMIT NUMBER: 086072
PERMIT NUMBER: 087613
MISCELLANEOUS DATE:

JUME MALAT RF1 MEST

--- BREATA AMALYDIG ---

THE RADIO INTERFERENCE

Operator Signature

party #85

2208-02

State of Missouri DEPARTMENT OF HEALTH



PERMIT TYPE II



FORREST GARTH

is hereby authorized to instruct and supervise operators, train instructors, inspect, calibrate, perform field repairs, and operate the following breath analyzer(s):

DATAMASTER

for the determination of the alcoholic content of blood from a sample of expired (alveolar) air. Issued under the provisions of sections 577.020 through 577.041, RSMo 1986.

providing of	377.020 Inrough 577.041, RSMo 1986,
02/26/08	5. 0 201
Number 820072	Director of State Minito Health & Angratory
Expires 02/26/2010	and
MO 580-0771 (7-88)	Director, Department of Health